



Intake System Installation Notes

- Air Intake Box is assembled but not ready for final installation. Prior to final installation remove top plate and apply a liberal amount of grease to air filter rubber seals and sealing surfaces.
- When installing hose couplers and clamps take care when clocking hose clamps to ensure proper range of motion of the throttle bodies.
- Use supplied bolt when mounting air intake temp sensor into intake top plate.
- A new support brace for the airbox is supplied along with the required hardware. Discard the factory unit.
- Remove the rubber line that goes from the top of the plastic oil tank breather to the factory air box. Install supplied mini air filter in its place
- 2019+ Only: Cut the vacuum line from the throttle body to the charcoal canister right below the oil tank on the passenger side. Install the check valve into that line with the flat side facing towards the charcoal canister:



- When removing the intake box, it is recommend that the open throttle body ports get covered to avoid getting debris in the engine
- Unplug the intake air temp sensor from the factory airbox, this is relocated to the DLP air intake
- A custom ECU calibration is highly recommended to maximize the performance of this air intake system. Beyond Redline Performance has done extensive dyno testing and can provide the best solution for your needs.
- Replacement air filter elements, pre-filters, and filter cleaning kits are available. Visit <https://dirtlaunchpowersports.com/> for this and more products for your Yamaha YXZ.

Thank you for your purchase, please contact us directly with any questions.

install factory
air temp sensor

clean air
for idle
speed motor

6mm bolt
some heads are not factory
tapped to 6x1.0 thread
user will need to perform
this if needed

6x1.0mm x 25
bolt and lock nut

8x 1.25mm x 30mm
bolt and lock nut
through factory
hole on block

